



Description

Lyte Master Beta Series are high quality aluminum heat sink to ensure ingenious shape and increase dissipation space. Dual anti-glare design, 360° adjustable, precision optical design, excellent solutions to replace the metal halide lamp. High quality isolated constant current driver. Dimming, intelligent control function for options.

FEATURES





- Housing - Die cast aluminium powder coated
- Reflector - Anodized aluminum reflector
- Diffuser - Tempered frosted glass or clear tempered glass
- Light Source: BridgeLux USA
- Life Span: 50,000 Hrs
- Operating Temp: -20°C to 50°C

Manufactured in accordance with all International Standards

Area of Application

Offices, Villas, Apartments, Stores & Malls

Product Model	Total Power	Lumen	CCT	Dimension L2xL1xH	Cut-Out
LM-004-CSMZ2CW-18W	18W	1800 Lm	6000K	116x222x90mm	100x200mm
LM-004-CSMZ2NW-18W	18W	1800 Lm	4000K	116x222x90mm	100x200mm
LM-004-CSMZ2WW-18W	18W	1800 Lm	3000K	116x222x90mm	100x200mm
LM-004-CSMZ2CW-30W	30W	3000 Lm	6000K	144x272x110mm	125x250mm
LM-004-CSMZ2NW-30W	30W	3000 Lm	4000K	144x272x110mm	125x250mm
LM-004-CSMZ2WW-30W	30W	3000 Lm	3000K	144x272x110mm	125x250mm
LM-004-CSMZ2CW-50W	50W	5000 Lm	6000K	164x313x113mm	145x290mm
LM-004-CSMZ2NW-50W	50W	5000 Lm	4000K	164x313x113mm	145x290mm
LM-004-CSMZ2WW-50W	50W	5000 Lm	3000K	164x313x113mm	145x290mm
LM-004-CSMZ2CW-70W	70W	7000 Lm	6000K	184x354x115mm	165x330mm
LM-004-CSMZ2NW-70W	70W	7000 Lm	4000K	184x354x115mm	165x330mm
LM-004-CSMZ2WW-70W	70W	7000 Lm	3000K	184x354x115mm	165x330mm



IP44	DALI	1-10 DIMMING	PHASE DIMMING
LM-80	LM-80	LED	COB
CRI >90	RoHS	CE	Series Wiring
85-265V 50/60Hz			
LED DRIVERS	TRIDONIC	Lyte Master	LED CHIPS: BRIDGELUX, CREE+