



FEATURES

- Housing: Die Cast aluminum powder coated.
- Reflector: Anodized Aluminium
- Diffuser: Tempered Glass
- Light Source: BridgeLux USA
- Life Span: 50,000 Hrs
- Operating Temp: -20°C to 50°C

Manufactured in accordance with all International Standards





Product Model	Total Power	Lumen	CCT	Dimension	Cut-Out
LM-022-DLZ3LCW-15W	15W	1500 Lm	6000K	Dia:108xH85mm	Dia:100mm
LM-022-DLZ3LNW-15W	15W	1500 Lm	4000K	Dia:108xH85mm	Dia:100mm
LM-022-DLZ3LWW-15W	15W	1500 Lm	3000K	Dia:108xH85mm	Dia:100mm
LM-022-DLZ3LCW-20W	20W	2000 Lm	6000K	Dia:120xH102mm	Dia:110mm
LM-022-DLZ3LNW-20W	20W	2000 Lm	4000K	Dia:120xH102mm	Dia:110mm
LM-022-DLZ3LWW-20W	20W	2000 Lm	3000K	Dia:120xH102mm	Dia:110mm
LM-022-DLZ3LCW-30W	30W	3000 Lm	6000K	Dia:140xH102mm	Dia:125mm
LM-022-DLZ3LNW-30W	30W	3000 Lm	4000K	Dia:140xH102mm	Dia:125mm
LM-022-DLZ3LWW-30W	30W	3000 Lm	3000K	Dia:140xH102mm	Dia:125mm
LM-022-DLZ3LCW-40W	40W	4000 Lm	6000K	Dia:160xH117mm	Dia:150mm
LM-022-DLZ3LNW-40W	40W	4000 Lm	4000K	Dia:160xH117mm	Dia:150mm
LM-022-DLZ3LWW-40W	40W	4000 Lm	3000K	Dia:160xH117mm	Dia:150mm

Description

Lyte Master Dazzle Pro LED down light adopts qualified super bright LEDs as light source, which are stable, long life and have no UV & IR emission. Can be mounted everywhere, thanks also to its easy installation requirements. This product takes care of the relevance of the human resources and of the environmental safety. The COB LED is specially chosen to provide high lumen results in uniform and pleasant light effect. It has different beam angles. The product is compatible with all leading sensor brands with dimming options in 0-10V or DALI.

Area of Application

Offices, Villas, Apartments, Stores & Malls



IK07			
IP40	DALI	1-10 DIMMING	PHASE DIMMING
LM-80	Energy Star	LED	COB
CRI >90	RoHS	CE	Series Wiring
85-265V 50/60Hz			
LED DRIVERS	TRIDONIC	Lyte Master	LED source: bridgeLux