



FEATURES

Housing: Die Cast aluminum powder coated.

Reflector: Anodized Aluminium

Diffuser: Tempered Glass

Light Source: BridgeLux USA

Life Span: 50,000 Hrs

Operating Temp: -20°C to 50°C

Manufactured in accordance with all International Standards





Product Model	Total Power	Lumen	CCT	Dimension	Cut-Out
LM-011-DLMV1CW-15W	15W	1500 Lm	6000K	Dia:115x107mm	Dia:100mm
LM-011-DLMV1NW-15W	15W	1500 Lm	4000K	Dia:115x107mm	Dia:100mm
LM-011-DLMV1WW-15W	15W	1500 Lm	3000K	Dia:115x107mm	Dia:100mm
LM-011-DLMV1CW-20W	20W	2000 Lm	6000K	Dia:115x107mm	Dia:100mm
LM-011-DLMV1NW-20W	20W	2000 Lm	4000K	Dia:115x107mm	Dia:100mm
LM-011-DLMV1WW-20W	20W	2000 Lm	3000K	Dia:115x107mm	Dia:100mm
LM-011-DLMV1CW-25W	25W	2500 Lm	6000K	Dia:140x145mm	Dia:125mm
LM-011-DLMV1NW-25W	25W	2500 Lm	4000K	Dia:140x145mm	Dia:125mm
LM-011-DLMV1WW-25W	25W	2500 Lm	3000K	Dia:140x145mm	Dia:125mm
LM-011-DLMV1CW-30W	30W	3000 Lm	6000K	Dia:140x145mm	Dia:125mm
LM-011-DLMV1NW-30W	30W	3000 Lm	4000K	Dia:140x145mm	Dia:125mm
LM-011-DLMV1WW-30W	30W	3000 Lm	3000K	Dia:140x145mm	Dia:125mm
LM-011-DLMV1CW-35W	35W	3500 Lm	6000K	Dia:165x160mm	Dia:150mm
LM-011-DLMV1NW-35W	35W	3500 Lm	4000K	Dia:165x160mm	Dia:150mm
LM-011-DLMV1WW-35W	35W	3500 Lm	3000K	Dia:165x160mm	Dia:150mm
LM-011-DLMV1CW-40W	40W	4000 Lm	6000K	Dia:165x160mm	Dia:150mm
LM-011-DLMV1NW-40W	40W	4000 Lm	4000K	Dia:165x160mm	Dia:150mm
LM-011-DLMV1WW-40W	40W	4000 Lm	3000K	Dia:165x160mm	Dia:150mm

Description

Lyte Master Jade Pro LED round down light adopts qualified super bright LEDs as light source, which are stable, long life and have no UV & IR emission. Available in a choice of options in a matter of design and power. This item is purely adaptable to every requirement. The high efficiency of the LED source ensures excellent performances and low consumptions. It has different beam angles. The product is compatible with all leading sensor brands with dimming options in 0-10V or DALI.

Area of Application

Offices, Villas, Apartments, Stores & Malls



IK07			
IP44	DALI	1-10 DIMMING	PHASE DIMMING
LM-80	LM-80	LED	COB
CRI >90	RoHS	CE	Series Wiring
85-265V 50/60Hz			
LED DRIVERS: TRIDONIC			

LED CHIPS: Lyte Master