

FEATURES

- Housing: Die Cast Aluminium with SS 309/316 trim.
- Diffuser: Tempered Glass.
- Reflector: Aluminium.
- Light Source: BridgeLux USA
- Life Span: 50,000 Hrs
- Operating Temp: -20°C to 50°C

Manufactured in accordance with all International Standards







Description

Lyte Master Flare in-ground linear light generates an effect. It can be used to immerse façades in light. Dark exterior areas become a thing of the past. The LED luminaire is well-designed, apparent like an object and achieves a maximum effect as a wall-washer for façade illumination.

Area of Application

Ramp Light, Wall Recessed, Walkway Light

Product Model	Total Power	Lumen	CCT	Dimension LxWxH	Cut-Out
LM-002-IGWW1CW-7W	7W	700 Lm	6000K	300x80x100mm	L292xW70mm
LM-002-IGWW1NW-7W	7W	700 Lm	4000K	300x80x100mm	L292xW70mm
LM-002-IGWW1WW-7W	7W	700 Lm	3000K	300x80x100mm	L292xW70mm
LM-002-IGWW1CW-11W	11W	1100 Lm	6000K	500x80x100mm	L492xW70mm
LM-002-IGWW1NW-11W	11W	1100 Lm	4000K	500x80x100mm	L492xW70mm
LM-002-IGWW1WW-11W	11W	1100 Lm	3000K	500x80x100mm	L492xW70mm
LM-002-IGWW1CW-21W	21W	2100 Lm	6000K	1000x80x100mm	L992xW70mm
LM-002-IGWW1NW-21W	21W	2100 Lm	4000K	1000x80x100mm	L992xW70mm
LM-002-IGWW1WW-21W	21W	2100 Lm	3000K	1000x80x100mm	L992xW70mm
LM-002-IGWW1CW-28W	28W	2800 Lm	6000K	1000x80x100mm	L992xW70mm
LM-002-IGWW1NW-28W	28W	2800 Lm	4000K	1000x80x100mm	L992xW70mm
LM-002-IGWW1WW-28W	28W	2800 Lm	3000K	1000x80x100mm	L992xW70mm
LM-002-IGWW1CW-36W	36W	3600 Lm	6000K	1000x80x100mm	L992xW70mm
LM-002-IGWW1NW-36W	36W	3600 Lm	4000K	1000x80x100mm	L992xW70mm
LM-002-IGWW1WW-36W	36W	3600 Lm	3000K	1000x80x100mm	L992xW70mm
LM-002-IGWW1CW-42W	42W	4200 Lm	6000K	1000x80x100mm	L992xW70mm
LM-002-IGWW1NW-42W	42W	4200 Lm	4000K	1000x80x100mm	L992xW70mm
LM-002-IGWW1WW-42W	42W	4200 Lm	3000K	1000x80x100mm	L992xW70mm



IK08			
IP67	DALI	1-10 DIMMING	PHASE DIMMING
LM-80	LED	COB	
CRI >90	RoHS	CE	Series Wiring
85-265V 50/60Hz			
LED DRIVERS	MW	TRIDONIC	Lyte Master