



## FEATURES

Housing: Die Cast Aluminium with SS 309/316 trim.

Diffuser: Tempered Glass.

Reflector: Aluminium.

Light Source: BridgeLux USA

Life Span: 50,000 Hrs

Operating Temp: -20°C to 50°C

**Manufactured in accordance with all International Standards**





| Product Model    | Total Power | Lumen  | CCT   | Dimension DxH | Cut-Out |
|------------------|-------------|--------|-------|---------------|---------|
| LM-002-UPE2CW-3W | 3W          | 300 Lm | 6000K | 116x90.4mm    | 102 mm  |
| LM-002-UPE2NW-3W | 3W          | 300 Lm | 4000K | 116x90.4mm    | 102 mm  |
| LM-002-UPE2WW-3W | 3W          | 300 Lm | 3000K | 116x90.4mm    | 102 mm  |
| LM-002-UPE3CW-4W | 4W          | 400 Lm | 6000K | 116x90.4mm    | 102 mm  |
| LM-002-UPE3NW-4W | 4W          | 400 Lm | 4000K | 116x90.4mm    | 102 mm  |
| LM-002-UPE3WW-4W | 4W          | 400 Lm | 3000K | 116x90.4mm    | 102 mm  |
| LM-002-UPE4CW-6W | 6W          | 600 Lm | 6000K | 116x90.4mm    | 102 mm  |
| LM-002-UPE4NW-6W | 6W          | 600 Lm | 4000K | 116x90.4mm    | 102 mm  |
| LM-002-UPE4WW-6W | 6W          | 600 Lm | 3000K | 116x90.4mm    | 102 mm  |
| LM-002-UPE5CW-8W | 8W          | 800 Lm | 6000K | 116x90.4mm    | 102 mm  |
| LM-002-UPE5NW-8W | 8W          | 800 Lm | 4000K | 116x90.4mm    | 102 mm  |
| LM-002-UPE5WW-8W | 8W          | 800 Lm | 3000K | 116x90.4mm    | 102 mm  |

## Description

Lyte Master Leo in-ground light with apertures offers a resourceful, indirect light option for all landscape lighting needs. Face plate uses stainless steel and the lampshade adopts high strength toughened glass. The light is bright, pure and uniform and the effect in the outdoor application is very good looking. Intended for installation in soil or gravel. The LED system provides very convenient quality.

## Area of Application

Wall Mounted, Outdoor, Pillar Mounted



|         |      |                   |              |               |
|---------|------|-------------------|--------------|---------------|
| IK08    | IP65 | DALI              | 1-10 DIMMING | PHASE DIMMING |
| LM-80   | RoHS | LED               | COB          | Series Wiring |
| CRI >90 | CE   | 85-265V   50/60Hz |              |               |

LED DRIVERS: MWM, TRIDONIC, Lyte Master  
LED CHIPS: bridgeLux, CREE+  
Lyte Master