



FEATURES

Housing: Aluminium Alloy with SS 309/316 trim.

Diffuser: Tempered Glass.

Reflector: Aluminium.

Light Source: BridgeLux USA

Life Span: 50,000 Hrs

Operating Temp: -20°C to 50°C

Manufactured in accordance with all International Standards



Product Model	Total Power	Lumen	CCT	Dimension LxWxH	Cut-Out
LM-003-IGRW7CW-7W	7W	700 Lm	6000K	1000x90x100mm	L992xW70mm
LM-003-IGRW7NW-7W	7W	700 Lm	4000K	1000x90x100mm	L992xW70mm
LM-003-IGRW7WW-7W	7W	700 Lm	3000K	1000x90x100mm	L992xW70mm
LM-003-IGRW7CW-11W	11W	1100 Lm	6000K	1000x90x100mm	L992xW70mm
LM-003-IGRW7NW-11W	11W	1100 Lm	4000K	1000x90x100mm	L992xW70mm
LM-003-IGRW7WW-11W	11W	1100 Lm	3000K	1000x90x100mm	L992xW70mm
LM-003-IGRW7CW-18W	18W	1800 Lm	6000K	1000x90x100mm	L992xW70mm
LM-003-IGRW7NW-18W	18W	1800 Lm	4000K	1000x90x100mm	L992xW70mm
LM-003-IGRW7WW-18W	18W	1800 Lm	3000K	1000x90x100mm	L992xW70mm
LM-003-IGRW7CW-21W	21W	2100 Lm	6000K	1000x90x100mm	L992xW70mm
LM-003-IGRW7NW-21W	21W	2100 Lm	4000K	1000x90x100mm	L992xW70mm
LM-003-IGRW7WW-21W	21W	2100 Lm	3000K	1000x90x100mm	L992xW70mm
LM-003-IGRW7CW-28W	28W	2800 Lm	6000K	1000x90x100mm	L992xW70mm
LM-003-IGRW7NW-28W	28W	2800 Lm	4000K	1000x90x100mm	L992xW70mm
LM-003-IGRW7WW-28W	28W	2800 Lm	3000K	1000x90x100mm	L992xW70mm
LM-003-IGRW7CW-36W	36W	3600 Lm	6000K	1000x90x100mm	L992xW70mm
LM-003-IGRW7NW-36W	36W	3600 Lm	4000K	1000x90x100mm	L992xW70mm
LM-003-IGRW7WW-36W	36W	3600 Lm	3000K	1000x90x100mm	L992xW70mm
LM-003-IGRW7CW-42W	42W	4200 Lm	6000K	1000x90x100mm	L992xW70mm
LM-003-IGRW7NW-42W	42W	4200 Lm	4000K	1000x90x100mm	L992xW70mm
LM-003-IGRW7WW-42W	42W	4200 Lm	3000K	1000x90x100mm	L992xW70mm

Description




Lyte Master Fusion in-ground linear light generates an effect. It can be used to immerse façades in light. Dark exterior areas become a thing of the past. The LED luminaire is well-designed, apparent like an object and achieves a maximum effect as a wall-washer for façade illumination.

Area of Application

Wall Mounted, Outdoor, Pillar Mounted



Size: L992*W70*H100mm



IK08			
IP67	DALI	1-10 DIMMING	PHASE DIMMING
LM-80	LED	COB	
CRI >90	RoHS	CE	Series Wiring
85-265V 50/60Hz			
LED DRIVERS	MW	TRIDONIC	Lyte Master

LED CHIPS: bridgeLux, CREE, Lyte Master