



Description

Lyte Master Bloom Bollard has the classic design of a bollard light, available with a curved top shape with glare reduction louvers to satisfy the details lovers. The light source is an LED high efficiency system, which ensures high performances while saving energy. All the items have features like easy installation, very low maintenance needs and full safety for electrical systems and people.

Area of Application

Facade & Garden

FEATURES

Housing: Die Cast Aluminium Powder coated.

Diffuser: Opal Polycarbonate.




Light Source: BridgeLux USA

Life Span: 50,000 Hrs

Operating Temp: -20°C to 50°C

Manufactured in accordance with all International Standards

Product Model	Total Power	Lumen	CCT	Dimension DxH
LM-011-FL7CW-10W	10W	1000 Lm	6000K	Dia:108x1000mm
LM-011-FL7NW-10W	10W	1000 Lm	4000K	Dia:108x1000mm
LM-011-FL7WW-10W	10W	1000 Lm	3000K	Dia:108x1000mm



IK07	IP66	DALI	1-10 DIMMING	PHASE DIMMING
LM-80	LED	COB	CRI >90	RoHS
CE	Series Wiring	85-265V 50/60Hz		
LED DRIVERS	MW	TRIDONIC	Lyte Master	LED CHIPS

bridgeLux CREE