



FEATURES

- Material: Flexible PCB
- Installation Tape: Mounting Clips and Channels.
- Light Source: BridgeLux USA
- Life Span: 40,000 Hrs
- Operating Temp: -20°C to 55°C
- Min Cutting Length: 10cm
- Manufactured in accordance with all International Standards**


Product Model	Total Power	Lumen	CCT	Dimension
LM-011-NF1XCW-14.4W	14.4W	1440 Lm	6000K	(W10xH20mm)x5Mtr
LM-011-NF1XNW-14.4W	14.4W	1440 Lm	4000K	(W10xH20mm)x5Mtr
LM-011-NF1XWW-14.4W	14.4W	1440 Lm	3000K	(W10xH20mm)x5Mtr

Description




Lyte Master Solo high-quality series of 24V LED Strip lights are an effective solution for creating attractive lighting effects in residential and commercial applications. Solo are versatile and can be used to highlight, decorate and add visibility to numerous settings. It has numerous wattages and a variety of LED numbers per meter, and a plethora of aluminum channels and diffuser types for contractors and end-users to choose from depending on their specific requirements.

Area of Application

Wall Mounted, Outdoor, Pillar Mounted



Dimensions can be Customized



IP67	DALI	1-10 DIMMING	PHASE DIMMING
LM-80	LM-80	LED	COB
CRI >90	RoHS	CE	Series Wiring
85-265V 50/60Hz			

LED DRIVERS: TRIDONIC Lyte Master

LED CHIPS: Lyte Master