



FEATURES

- Material: Double sided Flexible PCB
- IP65 Seal Out Material: Clear Silicon Rubber.
- Installation Tape: Strong Adhesive stick on tape.
- Light Source: BridgeLux USA
- Life Span: 40,000 Hrs
- Operating Temp: -20°C to 50°C

Manufactured in accordance with all International Standards





Product Model	Total Power	Lumen	CCT	Dimension
LM-011-SR5XCW-4.8W	4.8W	480 Lm	6000K	(W12xH4mm)x5Mtr
LM-011-SR5XNW-4.8W	4.8W	480 Lm	4000K	(W12xH4mm)x5Mtr
LM-011-SR5XWW-4.8W	4.8W	480 Lm	3000K	(W12xH4mm)x5Mtr
LM-011-SR5XCW-7.2W	7.2W	720 Lm	6000K	(W12xH4mm)x5Mtr
LM-011-SR5XNW-7.2W	7.2W	720 Lm	4000K	(W12xH4mm)x5Mtr
LM-011-SR5XWW-7.2W	7.2W	720 Lm	3000K	(W12xH4mm)x5Mtr
LM-011-SR5XCW-9.6W	9.6W	960 Lm	6000K	(W12xH4mm)x5Mtr
LM-011-SR5XNW-9.6W	9.6W	960 Lm	4000K	(W12xH4mm)x5Mtr
LM-011-SR5XWW-9.6W	9.6W	960 Lm	3000K	(W12xH4mm)x5Mtr
LM-011-SR5XCW-14.4W	14.4W	1440 Lm	6000K	(W12xH4mm)x5Mtr
LM-011-SR5XNW-14.4W	14.4W	1440 Lm	4000K	(W12xH4mm)x5Mtr
LM-011-SR5XWW-14.4W	14.4W	1440 Lm	3000K	(W12xH4mm)x5Mtr

Description

Lyte Master Ripple strip light is coming with SMD 5050 LED high quality chip and SMD 3030 LED high quality chip, to provide a bright, white and comfortable light with high CRI level →90. Available in the weatherproof IP65 with silicon glue cover or the Nano protection system IP68. It can be used in cove lighting, furniture lighting, accent lighting, kitchen cabinets etc.

Area of Application

Wall Mounted, Outdoor, Pillar Mounted



IP67	DALI	1-10 DIMMING	PHASE DIMMING
LM-80	LM-80	LED	COB
CRI >90	RoHS	CE	Series Wiring
85-265V 50/60Hz			
LED DRIVERS	MW	TRIDONIC	Lyte Master

LED CHIPS: bridgeLux, CREE, Lyte Master