



FEATURES

- Housing - Die cast aluminium powder coated
- Reflector - Back polished aluminium sheet.
- Diffuser - Made of PMMA Polycarbonate shock proof diffuser specially for LED
- LED - Reducing energy consumption with L80/B10/F10 50,000 hrs lifetime working under temp(-20°C To 50°C)

Manufactured in accordance with all International Standards





Product Model	Total Power	Lumen	CCT	Dimension
LM-011-SR5ZCW-4.8W	4.8W	480 Lm	6000K	(W10xH2mm)x5Mtr
LM-011-SR5ZNW-4.8W	4.8W	480 Lm	4000K	(W10xH2mm)x5Mtr
LM-011-SR5ZWW-4.8W	4.8W	480 Lm	3000K	(W10xH2mm)x5Mtr
LM-011-SR5ZCW-7.2W	7.2W	720 Lm	6000K	(W10xH2mm)x5Mtr
LM-011-SR5ZNW-7.2W	7.2W	720 Lm	4000K	(W10xH2mm)x5Mtr
LM-011-SR5ZWW-7.2W	7.2W	720 Lm	3000K	(W10xH2mm)x5Mtr
LM-011-SR5ZCW-9.6W	9.6W	960 Lm	6000K	(W10xH2mm)x5Mtr
LM-011-SR5ZNW-9.6W	9.6W	960 Lm	4000K	(W10xH2mm)x5Mtr
LM-011-SR5ZWW-9.6W	9.6W	960 Lm	3000K	(W10xH2mm)x5Mtr
LM-011-SR5ZCW-14.4W	14.4W	1440 Lm	6000K	(W10xH2mm)x5Mtr
LM-011-SR5ZNW-14.4W	14.4W	1440 Lm	4000K	(W10xH2mm)x5Mtr
LM-011-SR5ZWW-14.4W	14.4W	1440 Lm	3000K	(W10xH2mm)x5Mtr

Description

Lyte Master Izzy is IP20 strip light consisting of 60 (including RGB) or 120 LEDs/metre, mounted on a flexible adhesive circuit. The strip is suitable for any kind of application, since it may be folded or cut into 6-LED units without damaging the rest of the module. All tested. LEDs with different power and luminous intensity levels.

Area of Application

Wall Mounted, Cove, Pillar Mounted



IP20	DALI	1-10 DIMMING	PHASE DIMMING
LM-80	LM-80	LED	COB
CRI >90	RoHS	CE	Series Wiring
85-265V 50/60Hz			
LED DRIVERS	TRIDONIC	Lyte Master	LED CHIPS: bridgeLux, CREE+